

FARM HIGHWAY TOUGH - Especificaciones técnicas



Description

FARM HIGHWAY TOUGH es un neumático de alta velocidad proyectado para el cultivo del suelo y operaciones de transporte con remolques y maquinaria agrícola. Ofrece una elevada capacidad de carga incluso a altas velocidades. Además asegura un largo ciclo de vida del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	11L - 15 FI
LI/SS	128 J

Dimensions US Standard

Usa code	94032518
Ply Rating	12
Section Width (inch)	11
Overall Diameter (inch)	30.6
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	87.2
Rim Rec	8 LB
Rim Alt	10 LB ; 8 J
ECE	E11-54R-0017871

Load capacity (lbs)

mph / psi	90
62	3960

Printed on 27/04/2024 6:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..