

FL 252 - Especificaciones técnicas



Description

FL 252 es el neumático ideal para las operaciones de recolección de forraje con rastrillos hileradores y volteadoras de heno, así como para las operaciones logísticas con carretillas elevadoras. Este neumático garantiza una excelente duración, mientras que el específico dibujo de la banda de rodadura asegura la máxima estabilidad durante las operaciones de elevación.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Rastrillo hilerador rotativo

Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions International Standard

Ply Rating	10
Section Width (mm)	170
Overall Diameter (mm)	550
Rim Rec	4.00 E

Load capacity (Kg)

	km/h / bar	8.50
	25 LOAD WHEEL	1715
	25 STEER WHEEL	1320
	10 OTHER VEHICLES	1715
	25 OTHER VEHICLES	1320
	STATIC SIDE LOADER	1995

Printed on 19/04/2024 20:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..