

## FL 630 SUPER - Especificaciones técnicas



### Description

FL 630 SUPER es un neumático de flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	159 D

## Dimensions US Standard

Usa code	94060900
Section Width (inch)	24.1
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	139.1
Rim Rec	AG 20.00
ECE	E11-106R-005992

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3210	3600	4490	5100	5890	6680	7300	8000	8780
40	3530	3960	4930	5600	6470	7330	8010	8780	9645
30	4270	4790	5960	6780	7830	8870	9690	10630	11670
25	4790	5380	6690	7620	8800	9980	10890	11940	13120
15	5570	6260	7780	8850	10220	11600	12650	13880	15240
5	6340	7120	8860	10070	11640	13190	14420	15810	17360

Printed on 19/04/2024 3:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..