

FL 630 SUPER - Especificaciones técnicas



Description

FL 630 SUPER es un neumático de flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D

Dimensions US Standard

Usa code	94053445
Section Width (inch)	28.6
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	166.8
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-003009

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3850	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4230	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5130	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	5760	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	6690	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	7632	8820	10010	12150	14050	16190	18340	19760	21910	23810

Printed on 19/04/2024 3:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..