

FL 630 SUPER - Especificaciones técnicas



Description

FL 630 SUPER es un neumático de flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	750/60 R 30.5
LI/SS	181 D

Dimensions US Standard

Usa code	94041190
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	29.4
Rolling Circumference (inch)	201.4
Rim Rec	AG 24.00
ECE	E4-106R-001499

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	5300	6130	6960	8450	9780	11260	12750	13750	15230	16560
40	5820	6730	7640	9280	10740	12370	14010	15100	16730	18190
30	7050	8160	9250	11230	13000	14970	16970	18280	20260	22010
25	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
15	9200	10640	12070	14660	16960	19540	22130	23850	26440	28740
5	10480	12120	13760	16700	19320	22270	25210	27180	30120	32740

Printed on 19/04/2024 3:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..