

FL 633 PERFORMANCE - Especificaciones técnicas



Description

El nuevo neumático radial All Steel FL 633 PERFORMANCE combina perfectamente las exigencias de las diferentes aplicaciones agrícolas con la creciente demanda de logística en dicho sector. Proyectado particularmente para los camiones agrícolas, FL 633 PERFORMANCE es una solución innovadora que mejora las prestaciones de los tractores y los camiones para satisfacer las exigencias específicas de la agricultura moderna. Gracias a una carcasa muy robusta, una excepcional capacidad de carga y a su durabilidad, FL 633 PERFORMANCE marca el "nivel sucesivo" de los neumáticos Flotation, idóneos para utilizarlos en numerosas actividades agrícolas, así como para desplazarse por la autopista, alcanzando los 100 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Camión agrícola

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions US Standard

Usa code	94063581
Overall Width (inch)	23.2
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	140.1
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load capacity (lbs)

mph / psi	94
62	11000

Printed on 10/04/2024 2:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..