FL 639 - Especificaciones técnicas

Description

FL 639 es un neumático de flotación empleado principalmente en el campo idóneo para aplicaciones con pulverizadores. Su ancha huella garantiza una reducida compactación del suelo, favoreciendo una mayor productividad de los cultivos. La banda de rodadura reforzada y la protección del flanco contribuyen a un ciclo de vida más largo. FL 639 asegura una excelente tracción además de optimás propiedades de auto-limpieza.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Esparcidor

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	168 B/156 B
LI/SS DRIVE WHEEL	156 B
LI/SS FREE ROLLING	168 B

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	521
Rolling Circumference (mm)	3592
SRI (mm)	550
Rim Rec	AG 20.00
ECE	E11-106R-006478

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
50 FR	2180	2490	2800	3125	3450	3725	4000	4310	4625	4885	5150	5375	5600
50 DW	1550	1775	2000	2215	2430	2615	2800	3025	3250	3450	3650	3825	4000

Printed on 03/05/2024 12:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..