

FL 639 - Especificaciones técnicas



Description

FL 639 es un neumático de flotación empleado principalmente en el campo idóneo para aplicaciones con pulverizadores. Su ancha huella garantiza una reducida compactación del suelo, favoreciendo una mayor productividad de los cultivos. La banda de rodadura reforzada y la protección del flanco contribuyen a un ciclo de vida más largo. FL 639 asegura una excelente tracción además de optimas propiedades de auto-limpieza.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor

Version	STANDARD
Type	TL
Tyre Size	710/40 R 22.5
LI/SS	161 D/172 A8

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1140
Static Loaded Radius (mm)	503
Rolling Circumference (mm)	3492
SRI (mm)	550
Rim Rec	AG 24.00
ECE	E4-106R-000801

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1560	1770	2150	2485	2865	3245	3495	3875	4210
65	1480	1715	1945	2360	2730	3145	3565	3840	4255	4625
50	1795	2075	2355	2860	3305	3810	4315	4650	5155	5600
40	2015	2330	2645	3210	3715	4280	4845	5225	5790	6290
25	2340	2710	3075	3730	4315	4975	5630	6070	6730	7310
10	2665	3085	3500	4250	4915	5665	6415	6910	7660	8325

Printed on 20/04/2024 17:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..