

FL 695 - Ficha técnica



Description

FL 695 se ha diseñado específicamente para remolques en las aplicaciones de construcción y transporte agrícola con un patrón de banda de rodadura de bloque central único. Gracias a su robusta carcasa, FL 695 puede transportar cargas pesadas y mantener la estabilidad en todas las condiciones. Su profunda banda de rodadura garantiza una autolimpieza óptima durante las aplicaciones dentro y fuera de carretera. Las múltiples capas de cordón de acero refuerzan este patrón contra los pinchazos.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Remolque

Industrial: Remolque

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/55 R 26.5	STEEL BELTED	94072897	173 D			AG20.00		23.3	52.6	24.4	161	TL	E11-106R-007937
650/55 R 26.5	STEEL BELTED	94067886	178 D			AG20.00	AG22.00	24.8	54.7	24.8	167	TL	E11-106R-007052
600/60 R 30.5	STEEL BELTED	94073832	179 D	179 D	179 D	AG20.00		24.1	58.9	27.3	180.6	TL	E11-106R-008503
710/50 R 30.5	STEEL BELTED	94074082	177 D	177 D	177 D	AG24.00	AG20.00	27.6	58.7	27.2	179.3	TL	E11-106R-008661

Printed on 13/04/2024 2:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..