

FLOTATION 648 - Especificaciones técnicas



Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Esparcidor

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL | 151 A8/148 B |
| LI/SS FREE ROLLING | 163 A8/159 B |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94006359 |
| Ply Rating | 16 |
| Section Width (inch) | 19.7 |
| Overall Diameter (inch) | 46.1 |
| Static Loaded Radius (inch) | 20.1 |
| Rolling Circumference (inch) | 137.4 |
| Rim Rec | AG 16.00 |
| Rim Alt | 15.00 ; 17.00 |
| ECE | E4-106R-002308 |

Load capacity (lbs)

| mph / psi | 41 | 44 | 46 |
|-----------|-------|-------|-------|
| 5 FR | 13920 | 14490 | 15050 |
| 10 FR | 12530 | 13040 | 13550 |
| 20 FR | 11130 | 11600 | 12040 |
| 25 FR | 9940 | 10350 | 10750 |
| 30 FR | 8950 | 9310 | 9640 |
| 5 DW | 9840 | 10250 | 10650 |
| 10 DW | 8860 | 9230 | 9580 |
| 20 DW | 7880 | 8200 | 8520 |
| 25 DW | 7030 | 7320 | 7610 |
| 30 DW | 6330 | 6590 | 6940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 14:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..