

FLOTATION 648 - Especificaciones técnicas



Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Esparcidor

Version	STANDARD
Type	TL
Tyre Size	700/40 - 22.5
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 157 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	700
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	510
Rolling Circumference (mm)	3537
Rim Rec	AG 24.00
ECE	E11-106R-004554

Load capacity (Kg)

km/h / bar	1.50	1.60	1.70
10 FR	5850	6085	6300
20 FR	5265	5475	5670
30 FR	4680	4865	5040
40 FR	4180	4345	4500
50 FR	3760	3910	4125
10 DW	4100	4255	4410
20 DW	3690	3830	3970
30 DW	3280	3405	3530
40 DW	2930	3040	3150
50 DW	2635	2735	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 9:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..