

FLOTATION 648 - Especificaciones técnicas



Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Esparcidor

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	158 A8/155 B
LI/SS FREE ROLLING	170 A8/167 B

Dimensions US Standard

Usa code	94006557
Ply Rating	12
Section Width (inch)	31.5
Overall Diameter (inch)	54.8
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	164.8
Rim Rec	AG 28.00
ECE	E11-106R-004557

Load capacity (lbs)

mph / psi	22	23	25
5 FR	17210	17870	18520
10 FR	15490	16080	16670
20 FR	13770	14300	14810
25 FR	12290	12760	13230
30 FR	11070	11490	12010
5 DW	12190	12650	13120
10 DW	10970	11390	11810
20 DW	9750	10120	10490
25 DW	8710	9040	9370
30 DW	7840	8130	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 14:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..