FLOTATION 648 - Especificaciones técnicas

Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

US Standard

Construction

BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Esparcidor

Version	STANDARD
Type	TL
Tyre Size	850/50 - 30.5
LI/SS DRIVE WHEEL	168 A8/164 B
LI/SS FREE ROLLING	180 A8/176 B

Dimensions US Standard

Usa code	94006571
Ply Rating	12
Section Width (inch)	33.5
Overall Diameter (inch)	65
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 28.00
ECE	E11-106R-004564

Load capacity (lbs)

mph / psi	16	19	22
5 FR	20600	22720	24690
10 FR	18540	20450	22220
20 FR	16480	18180	19750
25 FR	14720	16230	17640
30 FR	13250	14600	15650
5 DW	14420	15890	17280
10 DW	12970	14310	15550
20 DW	11530	12720	13820
25 DW	10300	11350	12350
30 DW	9270	10220	11020

Printed on 19/04/2024 21:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..