

FLOTATION RIB 774 - Especificaciones técnicas



Description

FLOTATION RIB 774 es ideal para aplicaciones con ejes no motrices para la cosecha de heno y para los remolques. Ha sido proyectado para proporcionar óptimas prestaciones, reduciendo el tiempo que se tarda en las operaciones ofreciendo una elevada capacidad de carga así como una vida más larga del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS FREE ROLLING	160 A8/156 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E11-106R-005941

Load capacity (Kg)

km/h / bar	1.50	1.80	2.10
10 FR	5175	5755	6300
20 FR	4655	5180	5670
30 FR	4140	4605	5040
40 FR	3695	4110	4500
50 FR	3325	3700	4000

Printed on 06/05/2024 21:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..