

FLOTATION RIB 774 - Especificaciones técnicas



Description

FLOTATION RIB 774 es ideal para aplicaciones con ejes no motrices para la cosecha de heno y para los remolques. Ha sido proyectado para proporcionar óptimas prestaciones, reduciendo el tiempo que se tarda en las operaciones ofreciendo una elevada capacidad de carga así como una vida más larga del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS FREE ROLLING	167 A8/163 B

Dimensions US Standard

Usa code	94006618
Ply Rating	16
Section Width (inch)	21.7
Overall Diameter (inch)	48.8
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.7
Rim Rec	AG 16.00
ECE	E11-106R-005942

Load capacity (lbs)

mph / psi	35	38	41
5 FR	15370	16110	16820
10 FR	13830	14490	15130
20 FR	12300	12890	13460
25 FR	10980	11510	12010
30 FR	9880	10360	10750

Printed on 06/05/2024 19:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..