

FLOTATION RIB 774 - Especificaciones técnicas



Description

FLOTATION RIB 774 es ideal para aplicaciones con ejes no motrices para la cosecha de heno y para los remolques. Ha sido proyectado para proporcionar óptimas prestaciones, reduciendo el tiempo que se tarda en las operaciones ofreciendo una elevada capacidad de carga así como una vida más larga del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS FREE ROLLING	164 A8/160 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	600
Overall Diameter (mm)	1230
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3716
Rim Rec	AG 20.00
ECE	E11-106R-005943

Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500

Printed on 24/04/2024 21:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..