

# FLOTATION TR 675 - Especificaciones técnicas



## Description

FLOTATION TR 675 es ideal para las operaciones de transporte en el campo y por carretera. Este neumático es idóneo para utilizarlo en remolques y maquinaria agrícola. FLOTATION TR 675 ha sido proyectado para garantizar una excelente tracción, una capacidad de carga elevada y una vida mas larga del neumático.

## UM

International Standard

## Construction

 BIAS

## Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	151 A8/ 148 B
LI/SS FREE ROLLING	163 A8/159 B

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	515
Overall Diameter (mm)	1181
Static Loaded Radius (mm)	542
Rolling Circumference (mm)	3604
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-003605

## Load capacity (Kg)

km/h / bar	2.80	3.00	3.20
10 FR	6315	6575	6825
20 FR	5685	5915	6145
30 FR	5050	5260	5460
40 FR	4510	4695	4875
50 FR	4060	4225	4375
10 DW	4465	4650	4830
20 DW	4020	4185	4345
30 DW	3575	3720	3865
40 DW	3190	3320	3450
50 DW	2870	2990	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 16:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..