

FLOTATION TR 675 - Especificaciones técnicas



Description

FLOTATION TR 675 es ideal para las operaciones de transporte en el campo y por carretera. Este neumático es idóneo para utilizarlo en remolques y maquinaria agrícola. FLOTATION TR 675 ha sido proyectado para garantizar una excelente tracción, una capacidad de carga elevada y una vida mas larga del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/156 B

Dimensions US Standard

Usa code	94019809
Ply Rating	12
Section Width (inch)	21.7
Overall Diameter (inch)	49.6
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	143.3
Rim Rec	AG 16.00
ECE	E11-106R-004396

Load capacity (lbs)

mph / psi	22	26	30
5 FR	11410	12690	13890
10 FR	10260	11420	12500
20 FR	9130	10150	11110
25 FR	8150	9060	9920
30 FR	7330	8160	8820
5 DW	7980	8880	9720
10 DW	7180	8000	8750
20 DW	6380	7110	7780
25 DW	5700	6350	6940
30 DW	5130	5710	6170

Printed on 23/04/2024 10:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..