

## FLOTATION TR 675 - Especificaciones técnicas



### Description

FLOTATION TR 675 es ideal para las operaciones de transporte en el campo y por carretera. Este neumático es idóneo para utilizarlo en remolques y maquinaria agrícola. FLOTATION TR 675 ha sido proyectado para garantizar una excelente tracción, una capacidad de carga elevada y una vida mas larga del neumático.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	167 A8/163 B

## Dimensions US Standard

Usa code	94019816
Ply Rating	16
Section Width (inch)	21.7
Overall Diameter (inch)	49.6
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	143.3
Rim Rec	AG 16.00
ECE	E11-106R-004397

## Load capacity (lbs)

mph / psi	35	38	41
5 FR	15370	16110	16820
10 FR	13830	14490	15130
20 FR	12300	12890	13460
25 FR	10980	11510	12010
30 FR	9880	10360	10750
5 DW	10570	11080	11570
10 DW	9510	9980	10420
20 DW	8450	8860	9260
25 DW	7550	7910	8270
30 DW	6800	7120	7390

Printed on 20/04/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..