

## FLOTATION TR 678 - Ficha técnica



### Description

FLOTATION TR 678 ha sido particularmente desarrollado para la maquinaria agrícola y los remolques tanto para carretera como fuera de carretera. Permite transportar cargas pesadas a bajas presiones, asegurando al mismo tiempo una reducida compactación del suelo. Este neumático garantiza una excelente tracción y óptimas propiedades de auto-limpieza.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Remolque

| SIZE          | Version               | USACode  | LI/SS  | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC  | RIM ALT | SW   | OD   | SLR  | RC    | Type | ECE             |
|---------------|-----------------------|----------|--------|-------------------|--------------------|----|----------|---------|------|------|------|-------|------|-----------------|
| 320/60 - 12   | STANDARD              | 94067282 |        | 120 A8            | 132 A8             |    | 10.50 I  |         | 12.9 | 27.1 | 12.9 | 83.1  | TT   | E11-106R-006617 |
| 280/60 - 15.5 | STANDARD              | 94050154 | 128 A8 |                   |                    |    | 8.0      |         | 10.8 | 29.5 | 14.1 | 88.6  | TL   | E11-106R-004262 |
| 280/60 - 15.5 | STANDARD              | 94019922 | 115 A8 |                   |                    |    | 8.0      |         | 10.8 | 29.5 | 14.1 | 88.6  | TL   | E11-106R-004261 |
| 500/45 - 20   | STANDARD              | 94068906 |        | 148 A8            | 160 A8             |    | 16.00 DC |         | 19.5 | 38.6 | 0    | 0     | TL   | E11-106R-006816 |
| 600/40 - 22.5 | DUAL BEAD             | 94051915 |        | 157 A8            | 169 A8             | 20 | AG 20.00 |         | 24.2 | 42.7 | 19   | 128.5 | TL   | E11-106R-006501 |
| 600/40 - 22.5 | DUAL BEAD HD          | 94054152 |        | 157 A8            | 169 A8             | 20 | AG 20.00 |         | 24.2 | 42.7 | 19   | 128.5 | TL   | E11-106R-004619 |
| 600/40 - 22.5 | INDUSTRIAL            | 94051915 |        | 157 A8            | 169 A8             | 20 | AG 20.00 |         | 24.2 | 42.7 | 19   | 128.5 | TL   |                 |
| 650/45 - 22.5 | STANDARD              | 94026517 | 166 B  |                   |                    | 20 | AG 20.00 |         | 25.6 | 45.3 | 19.8 | 130   | TL   | E11-106R-004400 |
| 650/45 - 22.5 | STANDARD              | 94005420 | 160 D  |                   |                    |    | AG 20.00 |         | 25.6 | 45.3 | 19.8 | 130   | TL   | E11-106R-004399 |
| 650/45 - 22.5 | STEEL BELTED          | 94030170 | 166 B  |                   |                    | 20 | AG 20.00 |         | 25.6 | 45.3 | 19.8 | 130   | TL   | E11-106R-004401 |
| 710/40 - 22.5 | ARAMID + STEEL BELTED | 94064755 | 173 A8 |                   |                    |    | AG 24.00 |         | 27.8 | 45.9 | 0    | 0     | TL   | E11-106R-006011 |
| 710/40 - 22.5 | STEEL BELTED          | 94064755 | 173 A8 |                   |                    |    | AG 24.00 |         | 27.8 | 45.9 | 21.5 | 142.7 | TL   | E11-106R-006011 |

Printed on 23/02/2024 14:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..