

FLOTATION V LINE - Especificaciones técnicas



Description

FLOTATION V LINE ha sido específicamente desarrollado para utilizarlo en las operaciones de transporte con remolques. Este neumático se caracteriza por su elevada capacidad de flotación, asegurando una reducida compactación del suelo con el fin de proteger el terreno. FLOTATION V LINE permite transportar cargas pesadas a bajas presiones, optimizando la productividad.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL | 151 A8/ 148 B |
| LI/SS FREE ROLLING | 163 A8/159 B |

Dimensions International Standard

| | |
|-----------------------------------|----------------|
| Ply Rating | 16 |
| Section Width (mm) | 500 |
| Overall Diameter (mm) | 1170 |
| Static Loaded Radius (mm) | 510 |
| Rolling Circumference (mm) | 3489 |
| Rim Rec | AG 16.00 |
| Rim Alt | 15.00 ; 17.00 |
| ECE | E4-106R-001562 |

Load capacity (Kg)

| km/h / bar | 2.80 | 3.00 | 3.20 |
|------------|------|------|------|
| 10 FR | 6315 | 6575 | 6825 |
| 20 FR | 5685 | 5915 | 6145 |
| 30 FR | 5050 | 5260 | 5460 |
| 40 FR | 4510 | 4695 | 4875 |
| 50 FR | 4060 | 4225 | 4375 |
| 10 DW | 4465 | 4650 | 4830 |
| 20 DW | 4020 | 4185 | 4345 |
| 30 DW | 3575 | 3720 | 3865 |
| 40 DW | 3190 | 3320 | 3450 |
| 50 DW | 2870 | 2990 | 3150 |

Printed on 26/04/2024 6:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..