

FLOTATION V LINE - Ficha técnica



Description

FLOTATION V LINE ha sido específicamente desarrollado para utilizarlo en las operaciones de transporte con remolques. Este neumático se caracteriza por su elevada capacidad de flotación, asegurando una reducida compactación del suelo con el fin de proteger el terreno. FLOTATION V LINE permite transportar cargas pesadas a bajas presiones, optimizando la productividad.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 - 22.5	STANDARD	94006205	145 A8/142 B	157 A8/154 B	12	AG 16.00	15.00 ; 17.00	19.7	46.1	20.1	137.4	TL	E4-106R-001561
500/60 - 22.5	STANDARD	94006212	151 A8/ 148 B	163 A8/159 B	16	AG 16.00	15.00 ; 17.00	19.7	46.1	20.1	137.4	TL	E4-106R-001562
550/60 - 22.5	STANDARD	94006229	148 A8/144 B	160 A8/ 156 B	12	AG 16.00		21.7	48.8	21.3	146.7	TL	
550/60 - 22.5	STANDARD	94006236	154 A8/150 B	167 A8/163 B	16	AG 16.00		21.7	48.8	21.3	146.7	TL	E4-106R-001563

Printed on 26/04/2024 12:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..