

## FORESTLAND - Especificaciones técnicas



### Description

FORESTLAND es el modelo agroforestal más reciente e innovador de BKT. Este neumático diagonal ha sido diseñado específicamente para las labores más pesadas de las actividades forestales, pero también puede utilizarse en algunas operaciones agrícolas como el paisajismo y el corte y desbroce.

FORESTLAND es un neumático especialmente resistente gracias a su robusta carcasa de poliéster. La mezcla especial de la banda de rodadura es resistente a los cortes y los desgarros, además, su robusto flanco garantiza una larga vida útil del neumático incluso en las condiciones de uso más duras.

Si bien el diseño del hombro abierto favorece una excelente tracción en los terrenos blandos, el diseño especial de la banda de rodadura, así como sus bloques rígidos y reforzados, garantizan un buen agarre sobre cualquier terreno, además de elevadas propiedades de autolimpieza. Por otra parte, la robusta estructura del talón garantiza un alto nivel de estabilidad en las labores más duras.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	140 A8 / 137 B

## Dimensions US Standard

Usa code	94074716
Ply Rating	14
Section Width (inch)	14.9
Overall Diameter (inch)	53.7
Rim Rec	W 13
Rim Alt	W 12, W 11
TRA Code	LS2

## Load capacity (lbs)

mph / psi	44
25	5520
30	5080

Printed on 28/04/2024 1:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..