

GF 304 - Especificaciones técnicas



Description

GF 304 es un neumático idóneo para las aplicaciones para los carritos de golf. GF 304 asegura el máximo confort y una óptima protección de la turba. GF 304 también está disponible en la versión "aramid belted", con cinturones de aramida para proporcionar una mayor resistencia a la perforación.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Carro de golf

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	216
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003442

Load capacity (Kg)

km/h / bar	1.50
15	375

Printed on 20/04/2024 8:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..