

## GIANT TRAX - Especificaciones técnicas



### Description

GIANT TRAX ha sido desarrollado para las minicargadoras compactas (Skid Steer) que se utilizan sobre superficies desiguales como las que se pueden encontrar en los almacenes de chatarra y de reciclaje, así como en el sector minero. La banda de rodadura extra profunda con tacos más anchos y robustos asegura una óptima tracción, estabilidad y resistencia a la perforación. La especial mezcla de la banda de rodadura se traduce en una extraordinaria resistencia a los cortes y las laceraciones, así como una excelente resistencia contra el desgaste en cualquier tipo de terreno.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Minicargadora compacta

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	270
Overall Diameter (mm)	775
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2317
Rim Rec	8.25
ECE	E11-106R-003579

## Load capacity (Kg)

	km/h / bar	6.20
	10	2375
	15	1875
	25	1730

Printed on 22/04/2024 18:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..