

I - 1 - Especificaciones técnicas



Description

I-1 ha sido proyectado para actividades de transporte en el campo y la carretera, así como para los trabajos en el campo con maquinaria agrícola y remolques. I-1 es un neumático de alta velocidad que optimiza los tiempos de desplazamiento y permite poder concentrarse mejor en la propia actividad principal. El particular dibujo de la banda de rodadura asegura una vida operativa más larga incluso en las condiciones más difíciles y en presencia de rastros insidiosos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	21.5L - 16.1 SL
LI/SS	143 D

Dimensions International Standard

Ply Rating	8
Section Width (mm)	570
Overall Diameter (mm)	1150
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3510
Rim Rec	W 18 CH
Rim Alt	W 16 CH
ECE	E11-106R-006859
TRA Code	I1

Load capacity (Kg)

km/h / bar	1.70
65	2725

Printed on 23/04/2024 17:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..