

I - 1 - Especificaciones técnicas



Description

I-1 ha sido proyectado para actividades de transporte en el campo y la carretera, así como para los trabajos en el campo con maquinaria agrícola y remolques. I-1 es un neumático de alta velocidad que optimiza los tiempos de desplazamiento y permite poder concentrarse mejor en la propia actividad principal. El particular dibujo de la banda de rodadura asegura una vida operativa más larga incluso en las condiciones más difíciles y en presencia de rastros insidiosos.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	9.5L - 15 SL
LI/SS	121 D

Dimensions US Standard

Usa code	94006175
Ply Rating	12
Section Width (inch)	9.5
Overall Diameter (inch)	30.1
Static Loaded Radius (inch)	13.4
Rolling Circumference (inch)	88.3
Rim Rec	7.00
Rim Alt	8 LB
ECE	E11-106R-003370
TRA Code	11

Load capacity (lbs)

mph / psi	64
40	3200

Printed on 23/04/2024 18:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..