

INDUSTRIAL RIB F3 - Especificaciones técnicas



Description

INDUSTRIAL RIB F3 es un neumático agro-industrial con dibujo de bloques en la banda de rodadura proyectado para las actividades de transporte en el campo y la carretera, así como para los trabajos en el campo con maquinaria agrícola y remolques. Este neumático se caracteriza por una mezcla de extraordinaria resistencia a los rastrojos, por lo que es idóneo en las condiciones de trabajo más críticas y asegura un largo ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	11L - 16 SL
LI/SS	116 A6

Dimensions US Standard

Usa code	94000142
Ply Rating	10
Section Width (inch)	11
Overall Diameter (inch)	32.7
Rim Rec	W 8 L
Rim Alt	8 LB ; 10 LB ; W 10 L
ECE	E11-106R-004304
TRA Code	F3

Load capacity (lbs)

mph / psi	52
20	2760
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/02/2025 15:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..