

IT 400 - Especificaciones técnicas



Description

IT 400 es un neumático con un dibujo de bloques en la banda de rodadura que se utiliza principalmente por carretera en las actividades de transporte con plataformas bajas. Este neumático es idóneo para las aplicaciones de alta velocidad y garantiza significativos ahorros de carburante.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Remolque da plataforma baja

Version	STANDARD
Type	TT
Tyre Size	10.00 - 15
LI/SS	141/136 J

Dimensions US Standard

Usa code	94008254
Ply Rating	16
Section Width (inch)	10.8
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	108.1
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0018588

Load capacity (lbs)

mph / psi	125	115	105
10	9085	-	-
20	-	7495	-
62 LS	-	5675	-
62 LD	-	-	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 17:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..