

LG 307 - Especificaciones técnicas

Description

LG 307 es un neumático para el césped y la jardinería, idóneo para segadoras. El específico dibujo de la banda de rodadura hace que este neumático sea delicado en el terreno, previniendo daños al prado y facilitando al mismo tiempo la manipulación y las maniobras.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Segadora



Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	255
Overall Diameter (mm)	495
Static Loaded Radius (mm)	215
Rolling Circumference (mm)	1435
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005200

Load capacity (Kg)

km/h / bar	1.50
15	545

Printed on 23/04/2024 16:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..