

## LIFT STAR PLUS - Especificaciones técnicas



### Description

LIFT STAR PLUS es un neumático diagonal especialmente proyectado para los elevadores telescópicos que se utilizan en las operaciones más duras del sector de la construcción, así como en otras aplicaciones especialmente exigentes. El flanco de bajo perfil, garantiza una excelente estabilidad en las operaciones de levantamiento vertical, mientras que el dibujo no direccional de la banda de rodadura permite una mayor versatilidad en el montaje. Además, el flanco se ha desarrollado especialmente para asegurar una mayor resistencia a los cortes y los desgarros.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	400/75 - 28

## Dimensions US Standard

Usa code	94046225
Ply Rating	16
Section Width (inch)	15.7
Overall Diameter (inch)	51.9
Static Loaded Radius (inch)	23.3
Rolling Circumference (inch)	155.3
Rim Rec	12.00 GR
ECE	E11-106R-005330

## Load capacity (lbs)

mph / psi	51	73
30	8545	-
5	-	13890

Printed on 03/12/2023 19:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..