

## LIFTMAX LM 63 - Ficha técnica



### Description

El LIFTMAX LM 63 se ha desarrollado especialmente para operaciones industriales y de logística. El diseño de su banda de rodadura con 3 costillas ofrece una baja resistencia al rodamiento, un buen agarre en mojado y un desgaste uniforme, unidos a una mejor conducción. Se trata de un neumático radial All Steel con cinturones de acero multiestrato que proporciona una menor vibración, así como una estabilidad y un confort mejorados.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora

Industrial: Tow Tractor • Remolque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
<b>180/70 R 8 (18X7 R 8)</b>	STANDARD	94067008	125 A5	4.33R		6.7	18.1	TL	
<b>180/70 R 8 IMP (18X7 R 8)</b>	STANDARD	94067602	120 A8	4.33R		6.7	18.1	TL	E11-106R-006845
<b>6.00 R 9</b>	STANDARD	94063901	121 A5	4.00E		6.3	21.3	TL	
<b>6.50 R 10</b>	STANDARD	94066247	128 A5	5.00F	5.50 F	6.9	23.3	TL	
<b>7.00 R 12</b>	STANDARD	94066209	136 A5	5.00S		7.7	26.6	TL	
<b>7.00 R 15</b>	STANDARD	94066834	143 A5	5.50	5.00	7.8	29.1	TL	
<b>8.25 R 15</b>	STANDARD	94063635	153 A5	6.5	7.0	9.4	33.2	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/10/2024 2:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..