

## LOADER SPECIAL - Especificaciones técnicas



### Description

LOADER SPECIAL (L-5) es un neumático con estructura diagonal que mantiene las cargadoras en movimiento, asegurando una excelente eficiencia en las operaciones pesadas con rocas. Su óptima tracción y excepcional resistencia a los cortes darán un impulso a la productividad.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

## Dimensions US Standard

Usa code	94034536
Ply Rating	28
Overall Width (inch)	27
Overall Diameter (inch)	71.5
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	211.5
Rim Rec	22.00/3.0
TRA Code	L5

## Load capacity (lbs)

mph / psi	69
5	34200

Printed on 25/04/2024 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..