

LOADER SPECIAL - Ficha técnica



Description

LOADER SPECIAL (L-5) es un neumático con estructura diagonal que mantiene las cargadoras en movimiento, asegurando una excelente eficiencia en las operaciones pesadas con rocas. Su óptima tracción y excepcional resistencia a los cortes darán un impulso a la productividad.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Buldócer • Pala cargadora

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
20.5 - 25	STANDARD	94069958	L5	20	17.00/2.0		20.9	61.8	0	0	TL
26.5 - 25	STANDARD	94050406	L5	32	22.00/3.0		27	71.5	32.8	211.5	TL
26.5 - 25	STANDARD	94034536	L5	28	22.00/3.0		27	71.5	32.8	211.5	TL
29.5 - 25	STANDARD	94050413	L5	32	25.00/3.5		30.3	76	34.8	226.5	TL
29.5 - 25	STANDARD	94034734	L5	28	25.00/3.5		30.3	76	34.8	226.5	TL
35/65 - 33	STANDARD	94035991	L5	42	28.00/3.5		35.8	82.9	38.4	256.1	TL
40/65 - 39	STEEL BELTED	94075454	L5	56	32.00/4.0		39.4	94.7	0	0	TL
45/65 - 45	STEEL BELTED	94056903	L5	58	36.00/4.5		46.7	109.6	0	0	TL

Printed on 25/04/2024 20:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..