

## LT TR 182 - Especificaciones técnicas



### Description

LT TR 182 es idóneo para operaciones de transporte con camionetas. Este neumático de alta velocidad se utiliza principalmente por carretera y reduce netamente el consumo de carburante. Además, el neumático LT TR 182 es fácil de montar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Camión ligero

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	207
<b>Overall Diameter (mm)</b>	710
<b>Rim Rec</b>	6.00 MH

## Load capacity (Kg)

	km/h / bar	7.90
	100 LS	1375
	100 LD	1210

Printed on 13/09/2024 10:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..