

## LUG STAR - Especificaciones técnicas



### Description

LUG STAR es un neumático industrial desarrollado principalmente para aplicaciones carril-carretera con excavadoras que requieran una excelente tracción. Este neumático se caracteriza por las óptimas cualidades de auto-limpieza e la mezcla muy resistente de la banda de rodadura. Su robusta carcasa garantiza una duración superior.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Vehículo de carretera-ferrocarril

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

## Dimensions US Standard

Usa code	94056828
Ply Rating	14
Overall Width (inch)	11
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	131.6
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

## Load capacity (lbs)

mph / psi	73
30	5450

Printed on 20/04/2024 16:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..