

LUG STAR - Especificaciones técnicas



Description

LUG STAR es un neumático industrial desarrollado principalmente para aplicaciones carril-carretera con excavadoras que requieran una excelente tracción. Este neumático se caracteriza por las óptimas cualidades de auto-limpieza e la mezcla muy resistente de la banda de rodadura. Su robusta carcasa garantiza una duración superior.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Vehículo de carretera-ferrocarril

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94073580
Ply Rating	18
Overall Width (inch)	11
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	131.6
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (lbs)

mph / psi	145
5	15190
15	11685

Printed on 23/04/2024 8:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..