

MAGLIFT ECO RIB - Especificaciones técnicas



Description

MAGLIFT ECO RIB ha sido particularmente desarrollado para los remolques de equipos de apoyo en tierra. Su estructura reforzada elimina el riesgo de derrape, mientras que el especial borde de protección de la llanta protege el neumático contra daños. MAGLIFT ECO RIB ofrece un excelente control de la dirección, una elevada estabilidad, pocas vibraciones así como l'auto-alineación de remolque. Otras ventajas son la baja resistencia a la rodadura y una reducida generación de calor con una consecuente eficiencia mejorada.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrial: Carretilla elevadora

Version	STANDARD
Type	
Tyre Size	4.00 - 8

Dimensions International Standard

Section Width (mm)	104
Overall Diameter (mm)	406
Rim Rec	3.00 D - 8

Load capacity (Kg)

km/h / bar	-
5 OTHER VEHICLES	950
10 OTHER VEHICLES	860
25 OTHER VEHICLES	730

Printed on 25/04/2024 17:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..