

MAGLIFT ECO - Especificaciones técnicas



Description

MAGLIFT ECO ha sido particularmente desarrollado para utilizarlo con carretillas elevadoras. Este neumático se caracteriza para una elevada estabilidad y la distribución de la carga optimizada. Su estructura reforzada elimina el riesgo de derrape, mientras que el especial borde de protección de la llanta protege el neumático contra daños. MAGLIFT ECO asegura una excelente tracción y una baja resistencia al rodamiento y al calor con una consecuente eficiencia mejorada.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Carretilla elevadora

Version	LIP
Type	
Tyre Size	27 X 10 - 12 (250 / 75 - 12)

Dimensions US Standard

Usa code	94066094
Section Width (inch)	8.9
Overall Diameter (inch)	26.4
Rim Rec	8.00 G - 12

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	8595
15 STEER WHEEL	6615

Printed on 25/04/2024 5:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..