

MAGLIFT GROSS - Especificaciones técnicas



Description

El nuevo MAGLIFT GROSS se ha diseñado especialmente para tractores de obras y movimientos de semirremolques en aplicaciones industriales, principalmente en centros de distribución, centros logísticos y depósitos de contenedores. Su amplio perfil de la banda de rodadura proporciona una gran estabilidad lateral y una mayor seguridad en las operaciones de elevación y viraje, incluso con cargas pesadas. MAGLIFT GROSS se ha desarrollado con una estructura reforzada que elimina los riesgos de derrape, mientras que su forma especial del talón simplifica las operaciones de montaje sobre la llanta.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Tractor

Version	STANDARD
---------	----------

Type	
------	--

Tyre Size	355/50 - 20
-----------	-------------

Dimensions US Standard

Usa code	94070435
Section Width (inch)	12.2
Overall Diameter (inch)	33.1
Rim Rec	10.00 - 20

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	19775
15 STEER WHEEL	15210

Printed on 23/04/2024 13:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..