

## MINE STAR - Especificaciones técnicas



### Description

MINE STAR es un neumático de telas cruzadas que representa una óptima elección para realizar trabajos pesados en las minas. Este neumático se caracteriza para una alta resistencia a los cortes/desgarros y las perforaciones, optimizando la eficiencia operativa.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Vehículos para minería subterránea

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 38 X 16 - 15 |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94070008 |
| Ply Rating              | 32       |
| Section Width (inch)    | 15.7     |
| Overall Diameter (inch) | 39       |
| Rim Rec                 | 11.5     |

## Load capacity (lbs)

|           |       |
|-----------|-------|
| mph / psi | 145   |
| 5         | 14970 |

Printed on 24/04/2024 7:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..