

## MINE STAR - Especificaciones técnicas



### Description

MINE STAR es un neumático de telas cruzadas que representa una óptima elección para realizar trabajos pesados en las minas. Este neumático se caracteriza para una alta resistencia a los cortes/desgarros y las perforaciones, optimizando la eficiencia operativa.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Vehículos para minería subterránea

Version	STANDARD
Type	TL
Tyre Size	55 X 19.00 - 25

## Dimensions US Standard

Usa code	94067879
Ply Rating	50
Section Width (inch)	18.9
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	24.9
Rolling Circumference (inch)	168.5
Rim Rec	14.00
TRA Code	L5

## Load capacity (lbs)

mph / psi	145
3	38100
5	33800
10	31400
15	28700

Printed on 24/04/2024 13:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..