

MINEFORCE - Especificaciones técnicas



Description

MINEFORCE es un neumático de bandas diagonales diseñado especialmente para camiones de transporte en operaciones de minería y canteras. El neumático de alto rendimiento para camiones volquete MINEFORCE es la respuesta innovadora de BKT a los entornos mineros rocosos, abrasivos y duros. Tiene un exclusivo diseño de la banda de rodadura con compuestos desarrollados especialmente para condiciones mineras duras y rocosas. Su gran superficie de contacto con tacos rígidos proporciona un desgaste uniforme de la banda de rodadura y un ciclo de vida más largo.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dúmpster rígido

Version	CUT RESISTANT
Type	TL
Tyre Size	27.00 - 49

Dimensions International Standard

Ply Rating	66
TKPH	475
Overall Width (mm)	740
Overall Diameter (mm)	2695
Static Loaded Radius (mm)	1253
Rolling Circumference (mm)	7985
Rim Rec	19.50/4.0
TRA Code	E4
Tread Depth	68

Load capacity (Kg)

km/h / bar	7.25	10.00
50	29050	-
10	-	50790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/05/2025 9:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..