

MINEFORCE - Ficha técnica



Description

MINEFORCE es un neumático de bandas diagonales diseñado especialmente para camiones de transporte en operaciones de minería y canteras. El neumático de alto rendimiento para camiones volquete MINEFORCE es la respuesta innovadora de BKT a los entornos mineros rocosos, abrasivos y duros. Tiene un exclusivo diseño de la banda de rodadura con compuestos desarrollados especialmente para condiciones mineras duras y rocosas. Su gran superficie de contacto con tacos rígidos proporciona un desgaste uniforme de la banda de rodadura y un ciclo de vida más largo.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dúmper rígido

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 - 35	CUT RESISTANT	94069033	E4	48	17.00/3.5		25.8	86.2	39.5	255.2	TL	253
27.00 - 49	STANDARD	94070107	E4	48	19.50/4.0		29.1	106.1	49.3	314.4	TL	325
27.00 - 49	STANDARD	94069064	E4	54	19.50/4.0		29.1	106.1	49.3	314.4	TL	325

Printed on 23/04/2024 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..