

MP 567 - Especificaciones técnicas



Description

MP 567 es un neumático agro-industrial idóneo para desplazarse tanto por el campo como por la carretera, así como utilizarlo en los trabajos realizados en el sector de la municipalidad/mantenimiento. Es el neumático ideal para maquinaria agrícola y elevadores telescópicos. MP 567 ofrece una óptima tracción en todas las condiciones atmosféricas, así como excelentes propiedades de auto-limpieza. Este neumático asegura una experiencia de conducción confortable y un ciclo de vida más largo.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

Version	IMPLEMENT
Type	TL
Tyre Size	12.0/75 - 18 (300/75 - 18)
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	298
Overall Diameter (mm)	915
Static Loaded Radius (mm)	426
Rolling Circumference (mm)	2723
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-006701

Load capacity (Kg)

km/h / bar	4.00
40 FR	2430
40 DW	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 11:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..