

MP 585 - Especificaciones técnicas



Description

MP 585 es un neumático agro-industrial idóneo para los vehículos polivalentes que se utilizan en el sector de la municipalidad/mantenimiento. Este neumático ha sido específicamente proyectado con un dibujo de bloques que ofrece la máxima estabilidad y durabilidad en las condiciones operativas más difíciles, incluso a altas velocidades.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo universal

Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	335
Overall Diameter (mm)	1050
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3130
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022635

Load capacity (Kg)

km/h / bar	3.50
90	2000
50	2240

Printed on 23/05/2024 7:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..