

## MP 590 - Especificaciones técnicas



### Description

MP 590 es un neumático agro-industrial que se utiliza en las operaciones de carga con elevadores telescópicos y carretillas elevadoras. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como una durabilidad incrementada.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Elevador telescópico

Industrial: Carretilla elevadora • Elevador telescópico •

Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

## Dimensions International Standard

Ply Rating	20
Section Width (mm)	480
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3534
Rim Rec	14.0
ECE	E11-106R-004408

## Load capacity (Kg)

km/h / bar	7.50
40 DW	5800
30 DW	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 14:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..