

MP 600 - Especificaciones técnicas



Description

MP 600 es un neumático agro-industrial idóneo para las operaciones de carga con elevadores telescópicos y maquinaria agrícola. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como un prolongado ciclo de vida del producto.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

Version	SPECIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	1185
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3530
Rim Rec	13 SDC
Rim Alt	12

Load capacity (Kg)

km/h / bar	3.50
40 DW	3650
50 DW	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 9:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..