

## MULTI RIB - Ficha técnica



### Description

MULTI RIB es un neumático agro-industrial que se utiliza en los trabajos en el campo y en las operaciones de transporte con tractores 2WD/2RM y maquinaria agrícola. Este neumático ofrece una excepcional maniobrabilidad durante todo el ciclo de vida del producto. Hay disponibles varias versiones para satisfacer todas las exigencias: una versión "aramid belted" con cinturones de aramida, que proporcionan una mayor resistencia a la perforación y la versión "HD" con una mezcla especial que ofrece mayor resistencia a los cortes y los desgarros.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor 2WD • Maquinaria agrícola

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
11.00 - 16	ARAMID BELTED HD	12	W10 L	W 8 ; W 8 L	315	930	TL	E11-106R-005377
11.00 - 16	HD	12	W10 L	W 8 ; W 8 L	315	930	TL	
11.00 - 16	STANDARD	12	W10 L	W 8 ; W 8 L	315	930	TL	E11-106R-004649

Printed on 27/04/2024 12:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..