

## MULTIMAX MP 513 - Especificaciones técnicas



### Description

MULTIMAX MP 513 ha sido proyectado por BKT para utilizarlo con vehículos polivalentes en el sector de la municipalidad/mantenimiento y de transporte para uso agrícola y industrial. El neumático es perfecto para vehículos universales y camiones de fertilizante. Gracias a su robusta carcasa de nylon reforzada con cinturones de acero, MULTIMAX MP 513 permite transportar cargas pesadas a altas velocidades proporcionando una experiencia de conducción confortable. Asegura una vida operativa más larga así como optimas propiedades de auto-limpieza.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Vehículo universal • Camión de fertilizantes  
Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	425/55 R 17 MPT
LI/SS	134 G

## Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	900
Static Loaded Radius (mm)	399
Rolling Circumference (mm)	2695
Rim Rec	13
Rim Alt	13.00
ECE	E4-54R-0024098

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1080	1280	1550	1830	2120
65	1175	1390	1685	1990	2305
40	1245	1475	1785	2105	2440

Printed on 25/04/2024 18:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..